




Rillenkugellager einreihig ZKLN2557-2Z-INA - ZKLN2557-2Z-INA

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/zkln2557-2z-ina>

Axial angular contact ball bearings ZKLN2557-2Z
double direction, gap seals on both sides

E	25 mm	Tolerance: -0,005
D	57 mm	Tolerance: -0,010
B	28 mm	Tolerance: -0,25
	60 °	Contact angle
D_{2max}	48 mm	
d₂	40,5 mm	
d_{2min}	32 mm	
r_{1min}	0,6 mm	
r_{2in}	0,3 mm	
m	0,34 kg	Mass
C_d	27500 N	Basic dynamic load rating, axial
C_{0a}	50000 N	Basic static load rating, axial
n_{Grease}	4700 1/min	Limiting speed for grease lubrication
M_{fr}	0,2 Nm	Bearing frictional torque
S_a	750 kg/m	Axial rigidity
S_t	200 1/mmrad	Tilting rigidity
M₂	0,486 kg x cm ²	Mass moment of inertia for rotating inner ring
	2 µm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZM25	Designation of recommended INA locknut
	AM25	Designation of recommended INA locknut
		Locknuts not included in delivery.
M_s	25 Nm	Tightening torque
	9410 N	Axial preload force

PRODUKTMERKMALE

Marke	INA
N° Ean13	3663952334882
Innendurchmesser	25 mm
Wasserdichtheit	-
Außendurchmesser	57 mm
Dicke	28 mm
Verpackung	-

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE