




Rillenkugellager einreihig ZKLN70120-2Z-INA - ZKLN70120-2Z-INA

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/einreihig/zkln70120-2z-ina>

Axial angular contact ball bearings ZKLN70120-2Z
double direction, gap seals on both sides

d	70 mm	Tolerance: -0.008
D	120 mm	Tolerance: -0.015
B	45 mm	Tolerance: -0.25
	60 °	Contact angle
D_{1 max}	110 mm	
d₁	95 mm	
d_{2 max}	92 mm	
r_{1 max}	0.6 mm	
r_{2 max}	0.6 mm	
m	2.4 kg	Mass
C₁₀	85000 N	Basic dynamic load rating, axial
C_{10a}	281000 N	Basic static load rating, axial
n_{0.1 ref}	2300 1/min	Limiting speed for grease lubrication
M_{fr}	1.2 Nm	Bearing frictional torque
S₂₀	1400 N/mm	Axial rigidity
c₂₀	2250 Nm/rad	Tilting rigidity
M_r	19.8 kg x cm ²	Mass moment of inertia for rotating inner ring
	3 µm	Axial runout
	The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.	
	ZMA70110	Designation of recommended INA locknut
	AM70	Designation of recommended INA locknut
	Locknuts not included in delivery.	
M_t	130 Nm	Tightening torque
	Only valid in conjunction with INA precision locknuts	
	19171 N	Axial preload force

PRODUKTMERKMALE

Marke	INA
N° Ean13	3663952334974
Innendurchmesser	70 mm
Wasserdichtheit	Deckscheiben auf beiden Seiten
Außendurchmesser	120 mm
Dicke	45 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE