

Kegelrollenlager 6464-6420-B-TIMKEN - 6464-6420-B-TIMKEN

<https://www.123kugellager.de/kugellager-gehauselager/zyylinderrollenlager/kegelrollenlager/6464-6420-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF

| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|------------------------|--------------|------------------------|----------|-----------------------|-------|--------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic C ₁ | Factors e | Dynamic C ₂ | Factor K | Static C ₀ | Inner | Outer | | |
| mm | mm | mm | N | | N | N | N | | | | |
| 64.96 | 149.225 | 54.229 | 411000 | 0.30 | 107000 | 6000 | 143000 | 6464 | 6420 B | | |
| 2.5575 | 5.8750 | 2.1350 | 50400 | | 24000 | 14000 | 104000 | | | | |

| Bearing Dimensions | | | | Shaft | | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|---------|--------------------------|---------------------------------|-----------------------------|---|--------------------------------------|--------------------------------------|----------------|----------------|------------------|--------|-------|----------------|
| Width B | Width C | Eff. Ctr. d ₁ | Outer Ring Range D ₁ | Flange Width C ₁ | Max Shaft Fillet Radius (R ₁) | Seaking Shoulder Dia. d ₂ | Beading Shoulder Dia. D ₂ | G ₁ | G ₂ | C ₃ | | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | | | | | | |
| 54.229 | 44.450 | -15.0 | 107.060 | 7.000 | 3.5 | 61.0 | 67.0 | 148.0 | 158.0 | 28.1 | 0.2001 | 4.90 | |
| 2.1350 | 1.7500 | -0.59 | 4.1929 | 0.2725 | 0.14 | 2.39 | 2.62 | 5.91 | | | | 10.78 | |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | TIMKEN |
| N° Ean13 | 3663952338446 |
| Innendurchmesser | 64.96 mm |
| Außendurchmesser | 149.225 mm |
| Dicke | 54.229 mm |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE