


# Pendelkugellager 1209-K-TVH-C3-H209-FAG - 1209-K-TVH-C3-H209-FAG

<https://www.123kugellager.de/kugellager-gehauselager/rillenkugellager/pendelkugellager/1209-k-tvh-c3-h209-fag>

**Self-aligning ball bearings 1209-K-TVH-C3 + H209**  
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve



$d_{min}$	40 mm
D	85 mm
B	19 mm
$B_{min}$	5 mm
e	12 mm
$D_1$	72.7 mm
$D_{2max}$	78 mm
$D_2$	60 mm
d	45 mm
$d_1$	57.7 mm
$d_{2max}$	52 mm
$d_{2min}$	40 mm
I	33 mm
$F_{amax}$	1 mm
H209	Mass, adapter sleeve
m	0,454 kg Mass
$m_1$	0,22 kg Mass, adapter sleeve
C	22000 N Basic dynamic load rating, radial
e	0,21
$Y_1$	3,04
$Y_2$	4,7
$C_0$	7300 N Basic static load rating, radial
$Y_0$	3,18
$n_L$	9000 1/min Limiting speed
$n_R$	11100 1/min Reference speed
$C_1$	455 N Fatigue limit load, radial

## PRODUKTMERKMALE

Marke	FAG
N° Ean13	3663952346205
Innendurchmesser	40 mm
Außendurchmesser	85 mm
Dicke	19 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE