

Nadelhülsenlager TAW5545-Z-IKO - TAW5545-Z-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/taw5545-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS

Shaft dia. mm	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
55	TAW 5545 Z	250	—	—	—	—	—	—	—

Boundary dimensions mm		Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring		
F _w	D	C	f ₂ Max.	Shaft dia. h8		Housing bore dia. H7		N	N	IRT 5045-1			
				Min.	Max.	Min.	Max.						
55	67	45	3.4	55.000	54.981	67.018	66.988	—	—	79 900	172 000	5 500	IRT 5045-1

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952357379
Innendurchmesser	55 mm
Außendurchmesser	67 mm
Dicke	45 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE