



Nadelhülsenlager TAM5025-IKO - TAM5025-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/tam5025-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS

TAM TLAM

Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
50			TAM	5025	150					

Boundary dimensions mm	Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring				
	F _w	D	C	f ₂ Max.	Shaft dia. H7 Max. Min.	Housing bore dia. N7 Max. Min.								
50	62	25	3.4	3.4	50.000	49.984	62.018	61.988	—	—	49 100	89 000	6 500	IRT 4525

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 50% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952357454
Innendurchmesser	50 mm
Innendurchmesser	1.969" inch
Außendurchmesser	62 mm
Außendurchmesser	2.441" inch
Dicke	25 mm
Dicke	0.984" inch
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE