

# Nadelhülsenlager TAW6550-Z-IKO - TAW6550-Z-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/taw6550-z-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**

Shaft dia. mm	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
65	<b>TAW 6550 Z</b>	330	—	—	—	—	—	—	—

  

Boundary dimensions mm		Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring	
F <sub>w</sub>	D	Shaft dia. h8		Housing bore dia. H7		N7	N	N	rpm	IRT 5550		
65	77	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.			
		3.4	65.000	64.981	77.018	76.988	—	—	101 000	246 000	4 000	

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952357515
Innendurchmesser	65 mm
Außendurchmesser	77 mm
Dicke	45 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE