


Nadelhülsenlager YB66-IKO - YB66-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/yb66-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
9.525 ($\frac{3}{8}$)	—	—	—	—	YB 66	5.3	—	—	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring
F_w	D	C	Shaft dia. h8		Housing bore dia. J7		C	C_0	rpm	
			Max.	Min.	Max.	Min.	N	N		
9.525 ($\frac{3}{8}$)	14.288 ($\frac{1}{2}$)	9.52 (3/8)	9.525	9.516	14.288	14.280	6 920	9 410	16 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952361246
Innendurchmesser	9.525 mm
Außendurchmesser	14.288 mm
Dicke	9.52 mm
Gewicht	18 g
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE