


Nadelhülsenlager BHAM1614-IKO - BHAM1614-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bham1614-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
25.400 (1)	—	—	—	—	—	—	—	—	—	—	—	—	—
Boundary dimensions mm(inch) Standard mounting dimensions mm Basic dynamic load rating Basic static load rating Allowable rotational speed(*) Assembled inner ring F_w D C_1 t Shaft dia. h_8 Housing bore dia. $J7$ C C_0 rpm Max. Min. Max. Min. Max. Min. N N													
25.400	33.338	22.22	3.4	25.400	25.387	33.352	33.327	23 000	37 200	15 000	IRB 1214		

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952362021
Innendurchmesser	25.4 mm
Außendurchmesser	33.338 mm
Dicke	22.22 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE