

# Kegelrollenlager 641-632D-TIMKEN - 641-632D-TIMKEN

<https://www.123kugellager.de/kugellager-gehauselager/zyylinderrollenlager/kegelrollenlager/641-632d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDD

**TYPE TDD**

| Bearing Dimensions |         |         |                           | Load Ratings           |       |                       |      |                        |       |                       |        |
|--------------------|---------|---------|---------------------------|------------------------|-------|-----------------------|------|------------------------|-------|-----------------------|--------|
| Bore d             | O.D. D  | Width T | Double Outer Ring Width C | Dynamic <sup>(1)</sup> |       | Static <sup>(2)</sup> |      | Dynamic <sup>(3)</sup> |       | Factor <sup>(4)</sup> |        |
| mm                 | mm      | mm      | mm                        | C <sub>10</sub>        | N     | C <sub>0</sub>        | N    | C <sub>90</sub>        | N     | C <sub>50</sub>       | K      |
| 66.675             | 136.525 | 95.250  | 76.200                    | 40100                  | 33000 | 0.35                  | 1.86 | 2.78                   | 71600 | 44400                 | 125000 |
| 2.6200             | 5.3750  | 3.7500  | 3.0000                    |                        |       |                       |      |                        | 10100 | 6900                  | 28000  |

  

| Part Number |       | Shaft                                   |                                      |   |                                      | Housing        |                |                |                | Pin            |                | Geometry Factors |               |  | Bearing Weight |
|-------------|-------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|---------------|--|----------------|
| Inner       | Outer | Max. Shaft Fillet Radius R <sub>f</sub> | Backing Shoulder Dia. d <sub>s</sub> | Max. Housing Fillet Radius r <sub>h</sub> | Backing Shoulder Dia. D <sub>s</sub> | K <sub>1</sub> | K <sub>2</sub> | G <sub>1</sub> | G <sub>2</sub> | C <sub>1</sub> | C <sub>2</sub> |                  |               |  |                |
| 641         | 632D  | 3.5<br>0.14                             | 63.0<br>3.27                         | 1.5<br>0.06                               | 125.0<br>4.92                        | -              | -              | 105.4          | 21.0           | 0.3814         |                |                  | 8.86<br>13.35 |  |                |

## PRODUKTMERKMALE

|                  |               |
|------------------|---------------|
| Marke            | TIMKEN        |
| N° Ean13         | 3663952362274 |
| Innendurchmesser | 66.675 mm     |
| Außendurchmesser | 136.525 mm    |
| Dicke            | 95.25 mm      |
| Verpackung       | 1             |

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE