


# Nadelhülsenlager YB2016-IKO - YB2016-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/yb2016-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
31.750 (1 1/4)	—	—	—	—	—	—	—	—	YB 2016 57		
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
$F_w$	$D$	$C_0$	$t_0$	Shaft dia. mm	Housing bore dia. mm	$C$	$C_0$	N	N	rpm	IRB 1616
31.750	38.100	25.40	—	31.750	31.734	38.114	38.089	40 900	100 000	4 500	IRB 1616

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952362359
Innendurchmesser	31.75 mm
Außendurchmesser	38.1 mm
Dicke	25.4 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE