


Nadelhülsenlager BAM228-IKO - BAM228-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/nadelhulsenlager/bam228-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g																																							
	Standard	Mass (Ref.) g	Closed end																																																	
34.925 (1 3/8)	---	---	---	---	---	---	---	---	---	---	---	---	---																																							
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions mm(inch)</th> <th colspan="4">Standard mounting dimensions mm</th> <th>Basic dynam. load rating</th> <th>Basic static load rating</th> <th>Allowable rotational speed^(*)</th> <th>Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>Shaft dia. h8</th> <th>Housing bore dia. J7</th> <th>Max.</th> <th>Min.</th> <th>C</th> <th>C₀</th> <th>N</th> <th>N</th> <th>rpm</th> <th colspan="2">IRB 188</th> </tr> </thead> <tbody> <tr> <td>34.925</td> <td>41.275</td> <td>12.70</td> <td>34.925</td> <td>34.909</td> <td>41.289</td> <td>41.264</td> <td>9 770</td> <td>16 600</td> <td>10 000</td> <td colspan="2"></td> <td colspan="2"></td> </tr> </tbody> </table>														Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynam. load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring	F _w	D	C	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	C	C ₀	N	N	rpm	IRB 188		34.925	41.275	12.70	34.925	34.909	41.289	41.264	9 770	16 600	10 000				
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynam. load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring																																										
F _w	D	C	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	C	C ₀	N	N	rpm	IRB 188																																								
34.925	41.275	12.70	34.925	34.909	41.289	41.264	9 770	16 600	10 000																																											

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952363035
Innendurchmesser	34.925 mm
Außendurchmesser	41.275 mm
Dicke	12.7 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE