


Nadellager GBRI61812-IKO - GBRI61812-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbri61812-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F_w</i>
9.525 (3/8)	GBRI 61812	74	9.525 $\frac{1}{2}$	28.575 $1 \frac{1}{8}$	19.050 $\frac{3}{4}$	19.300	15.875 $\frac{5}{8}$

Standard mounting dimensions mm				Basic dynamic load rating <i>C</i>	Limiting static rating <i>C₀</i>	Allowable rotational speed (1) rpm	Assembled inner ring
<i>d_a</i>	<i>D_a</i>	<i>r_a</i> max	<i>r_{es}</i> max				
Min.	Max.	Max.	Max.	N	N		LRBZ 61012
14	14.5	24.5	0.6	23 500	28 500	9 500	

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377377
Innendurchmesser	9.525 mm
Innendurchmesser	3/8" inch
Außendurchmesser	28.575 mm
Außendurchmesser	1 1/8" inch
Dicke	19.3 mm
Dicke	0.76" inch
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE