


# Nadellager GBR1223520-IKO - GBR1223520-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbri223520-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F<sub>w</sub></i>
<b>34.925</b> (1 1/8)	<b>GBR1 223520</b>	316	34.925 $\pm 0.015$	55.562 $\pm 0.025$	31.750 $\pm 0.025$	32.000	41.275 $\pm 0.025$

Standard mounting dimensions mm		Basic dynamic load rating <i>C</i>	Limiting static rating <i>C<sub>0</sub></i>	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring		
<i>d<sub>a</sub></i>	<i>D<sub>a</sub></i>						
Min.	Max.	<i>r<sub>as max</sub></i> <sup>(*)</sup>	<i>N</i>	<i>N</i>			
40.2	40.2	50.5	0.6	67 000	130 000	3 500	<b>LRBZ 222620</b>

Notes: <sup>(\*)</sup> Maximum permissible corner radius of the housing.  
<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
 Remarks: 2. The outer ring has an oil groove and an oil hole.  
 2. No grease is preapplied. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377490
Innendurchmesser	34.925 mm
Außendurchmesser	55.562 mm
Dicke	32 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE