


Nadellager GBR648032-IKO - GBR648032-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbr648032-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (¹⁾)	
			F _o	D	C	D _s Max.	r _{as max}
101.600 (4)	GBR 648032	1 500	101.600	127.000.5	50.800.2	119	1.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed(²⁾)					
N	N	rpm					
237 000	556 000	1 500					

Notes:
(¹) Maximum permissible corner radius of the housing.
(²) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377674
Innendurchmesser	101.6 mm
Außendurchmesser	127 mm
Dicke	50.8 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE