


# Nadellager GBR202816-IKO - GBR202816-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbr202816-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ( <sup>(1)</sup> )	
			F <sub>o</sub>	D	C	D <sub>s</sub> Max.	r <sub>as max</sub>
<b>31.750</b> (1 1/4)	<b>GBR 202816</b>	128	31.750( <sup>(1)</sup> / <sub>2</sub> )	44.450( <sup>(1)</sup> / <sub>2</sub> )	25.400(1)	39.6	0.6
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
N	N	rpm					
46 600	83 900	4 500					

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377766
Innendurchmesser	31.75 mm
Außendurchmesser	44.45 mm
Dicke	25.4 mm
Gewicht	133 g
Verpackung	1
Standard	Ohne Standard

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE