


Nadellager GBR283820-IKO - GBR283820-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbr283820-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F _d	D	C	D _s Max.	r _{as max}
44.450 (1 3/4)	GBR 283820	275	44.450 ⁽¹⁾	60.325 ⁽²⁾	31.750 ⁽¹⁾	55.3	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽³⁾					
N	N	rpm					
69 700	141 000	3 500					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-applied. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377834
Innendurchmesser	44.45 mm
Außendurchmesser	60.325 mm
Dicke	31.75 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE