


Nadellager GBRI325228-IKO - GBRI325228-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbri325228-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
50.800 (2)	GBRI 325228	1 030	50.800 ₀	82.550 _{0.010}	44.450 _{0.001}	44.700	63.500 _{0.001}

Standard mounting dimensions mm		Basic dynamic load rating C ₀ N	Basic static load rating C ₀ N	Allowable rotational speed (P) rpm	Assembled inner ring
d _a Min. Max.	D _a Min. Max.				
58 61	75.7	141 000	306 000	2 500	LRBZ 324028

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377902
Innendurchmesser	50.8 mm
Außendurchmesser	82.55 mm
Dicke	44.45 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE