

# Nadellager RNA49-28-U-IKO - RNA49-28-U-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/rna49-28-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_s$ (1)
32	—	<b>RNA 49/28U</b>	—	—	75.5	32	45	17	0.3

Standard rounding dimension $D_s$ Max. mm	Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed (reference speed) rpm
43	21 000	26 800	6 000

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952379067
Innendurchmesser	32 mm
Außendurchmesser	45 mm
Dicke	17 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE