

Nadellager RNA49-62-U-IKO - RNA49-62-U-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/rna49-62-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|---|--|---|---|---------------|---------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_1 (1) |
| 70 | — | RNA 49/62U | — | — | 320 | 70 | 88 | 25 | 1 |
| Standard rounding dimension D_1 Max. mm | | | | | | | | | |
| | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed (reference speed) rpm | | | | | | |
| 83 | 55 700 | 96 300 | 2 500 | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
 Allowable rotational speed applies to grease lubrication.
 Remarks: 1. The outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952379524 |
| Innendurchmesser | 70 mm |
| Außendurchmesser | 88 mm |
| Dicke | 25 mm |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE