

Nadellager RNA6913-U-IKO - RNA6913-U-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/rna6913-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref) g | Boundary dimensions mm | | | |
|--|---------------------------------------|--|---------------------------------------|---------------|-----------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_s (1) |
| 72 | — | — | RNA 6913UU | — | 580 | 72 | 90 | 45 | 1 |
| Standard mounting diameter D_s Max. mm | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed (2) rpm | | | | | | |
| 85 | 97 400 | 200 000 | 2 500 | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952380148 |
| Innendurchmesser | 72 mm |
| Innendurchmesser | 2.835" inch |
| Außendurchmesser | 90 mm |
| Außendurchmesser | 3.543" inch |
| Dicke | 45 mm |
| Dicke | 1.772" inch |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE