

Nadellager NA6902-U-IKO - NA6902-U-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/na6902-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
15	—	—	—	—	NA 6902U	62.5	15	28	23	24

r_s min (¹⁾)	F_w	Standard mounting dimensions mm			Basic static load rating C_0 N	Basic dynamic load rating C_1 N	Allowable rotational speed (²⁾) rpm	Assembled inner ring
		Min.	Max.	d_s				
0.3	20	17	19	26	18 500	27 100	9 500	LRTZ 152024

Notes: (¹) Minimum allowable value of chamfer dimension r
(²) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952381138
Innendurchmesser	15 mm
Außendurchmesser	28 mm
Dicke	24 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE