

Nadellager NA4924-U-IKO - NA4924-U-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/na4924-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|------------------|-----------------------|---------------|----------------|---------------|---------------------|---------------------------|-----|----|----|
| | With two seals | With one seal | With two seals | With one seal | | d | D | C | B |
| 120 | — | NA 4924U | — | — | 2 990 | 120 | 165 | 45 | 46 |

| r _s mm | F _w | Standard mounting dimensions mm | | Basic static load rating C ₀ | Basic dynamic load rating C | Allowable rotational speed ⁽¹⁾ rpm | Assembled inner ring | |
|-------------------|----------------|------------------------------------|---------------------|--|--------------------------------|--|----------------------|---------------|
| | | d _s Min. | d _s Max. | | | | | |
| 1.1 | 135 | 126.5 | 133 | 158.5 | 178 000 | 410 000 | 1 400 | LRTZ 12013546 |

Notes: (1) Minimum allowable value of shaft diameter r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952382029 |
| Innendurchmesser | 120 mm |
| Innendurchmesser | 4.724" inch |
| Außendurchmesser | 165 mm |
| Außendurchmesser | 6.496" inch |
| Dicke | 46 mm |
| Dicke | 1.811" inch |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE