


Nadellager BR486028-U-IKO - BR486028-U-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/br486028-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
76.200 (3)		BR 486028 U	585	76.200 (3)	95.250 (3 7/8)	44.450 (1 3/4)
Standard mounting dimensions mm		Basic dynamic load rating C	Static load rating C_0	Allowable rotational speed ^(*)		
D_1 Max.	r_{as} max (^(†))	N	N	rpm		
87.0	2.0	105 000	211 000	2 500		

Notes: (†) Minimum allowable value of chamfer dimension r .
(*) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382388
Innendurchmesser	76.2 mm
Außendurchmesser	95.25 mm
Dicke	44.45 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE