

Nadellager BRI61816-UU-IKO - BRI61816-UU-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/bri61816-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
9.525 (3/8)	BRI 61816 UU		78	9.525 (3/8)	28.575 (1 1/8)	25.400 (1)	25.650
F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ^(*) rpm	Assembled inner ring	
	Min.	Max.				Min.	Max.
	14	24.5	18 300	20 000	12 000	LRBZ 61016 B	

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382463
Innendurchmesser	9.525 mm
Innendurchmesser	3/8" inch
Außendurchmesser	28.575 mm
Außendurchmesser	1 1/8" inch
Dicke	25.4 mm
Dicke	1" inch
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE