

## Nadellager BRI102216-U-IKO - BRI102216-U-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/bri102216-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>15.875</b> ( $\frac{3}{4}$ )		<b>BRI 102216 U</b>	113.5	15.875 ( $\frac{3}{4}$ )	34.925 (1 $\frac{3}{4}$ )	25.400 (1 )	25.650
$F_w$	Standard mounting dimensions (mm)			Ball dynamic load rating C N	Ball static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRBZ 101416 B
	Min.	Max.	Max. as max. <sup>(1)</sup>				
<b>22.225</b> ( $\frac{7}{8}$ )	21	21.2	29.7	0.6	21 600	26 900	9 000

Notes:  
(1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark:  
1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382517
Innendurchmesser	15.875 mm
Außendurchmesser	34.925 mm
Dicke	25.4 mm
Gewicht	150 g
Verpackung	-
Standard	-

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE