


Nadellager BRI142620-UU-IKO - BRI142620-UU-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/bri142620-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
22.225 ($\frac{3}{4}$)	BRI 142620 UU		177	22.225 (1 $\frac{3}{4}$)	41.275 (1 $\frac{3}{4}$)	31.750 (1 $\frac{3}{4}$)	32.000	
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRBZ 141820 B	
	Min.	Max.	Max. as max. ⁽¹⁾					
28.575 (1 $\frac{3}{4}$)	27	27.5	36.0	34 900	49 900	7 000		

Notes:
(1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382548
Innendurchmesser	22.225 mm
Außendurchmesser	41.275 mm
Dicke	31.75 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE