

Nadellager BRI142620-U-IKO - BRI142620-U-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/bri142620-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
22.225 ($\frac{9}{4}$)		BRI 142620 U	177	22.225 ($\frac{9}{4}$)	41.275 (1 $\frac{7}{8}$)	31.750 (1 $\frac{1}{4}$)	32.000	
F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring		
	Min.	Max.					Min.	Max.
	27	36.0	34 900	49 900	7 000	LRBZ 141820 B		

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382555
Innendurchmesser	22.225 mm
Außendurchmesser	41.275 mm
Dicke	31.75 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE