


# Nadellager BRI183020-U-IKO - BRI183020-U-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/bri183020-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>28.575</b> (1 1/8)		<b>BRI 183020 U</b>	211	28.575 (1 1/8)	47.625 (1 7/8)	31.750 (1 1/4)	32.000	
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring	
	Min.	Max.	as max. <sup>(*)</sup>					
34.925 (1 3/8)	33.5	33.9	42.4	0.6	38 500	60 000	5 500	LRBZ 182220 B

Notes: (\*) Minimum allowable value of chamfer dimension r.  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382593
Innendurchmesser	28.575 mm
Außendurchmesser	47.625 mm
Dicke	31.75 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE