

Nadellager

GBR162416-UU-IKO - GBR162416-UU-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbr162416-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
25.400 (1)	GBR 162416 UU		99	25.400 (1)	38.100 (1 1/2)	25.400 (1)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball dynamic load rating C_0	Allowable rotational speed ⁽²⁾		
D_s Max.	r as max (°)	N	N	rpm		
33.3	0.6	31 000	46 100	3 000		

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382906
Innendurchmesser	25.4 mm
Außendurchmesser	38.1 mm
Dicke	25.4 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE