

Nadellager

GBR202820-UU-IKO - GBR202820-UU-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbr202820-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | |
|---------------------------------|-----------------------|---------------------------------|----------------------------------|---|----------------|----------------|
| | With two seals | With one seal | | F_w | D | C |
| 31.750 (1.250) | GBR 202820 UU | | 152 | 31.750 (1.250) | 44.450 (1.750) | 31.750 (1.250) |
| Standard mounting dimensions mm | | Seal dynamic load rating C | Ball static load rating C_0 | Allowable rotational speed ^(*) | | |
| D_s | r as max | N | N | rpm | | |
| 39.6 | 0.6 | 46 600 | 83 900 | 2 500 | | |

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952382951 |
| Innendurchmesser | 31.75 mm |
| Außendurchmesser | 44.45 mm |
| Dicke | 31.75 mm |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE