

# Nadellager

## GBR243320-UU-IKO - GBR243320-UU-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbr243320-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		$F_w$	$D$	$C$
<b>38.100</b> (1.5)	<b>GBR 243320 UU</b>		200	38.100(1.5)	52.388(2.06)	31.750(1.25)
Standard mounting dimensions mm		Ball dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_s$ Max.	$r$ as max (°)	N	N	rpm		
47.3	0.6	54 200	97 700	2 000		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(°) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382999
Innendurchmesser	38.1 mm
Außendurchmesser	52.388 mm
Dicke	31.75 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE