

Nadellager GBR263520-U-IKO - GBR263520-U-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbr263520-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		F_w	D	C
41.275 (1 5/8)	GBR 263520 UU		215	41.275 (1 7/8)	55.562 (2 1/8)	31.750 (1 1/4)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_s Max.	r as max (^(†))	N	N	rpm		
50.5	0.6	56 600	105 000	1 900		

Notes: (*) Minimum allowable value of diameter dimension r
(†) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952383019
Innendurchmesser	41.275 mm
Außendurchmesser	55.562 mm
Dicke	31.75 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE