

# Nadellager

## GBR486028-UU-IKO - GBR486028-UU-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/gbr486028-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		$F_w$	$D$	$C$
<b>76.200</b> (3)	<b>GBR 486028 UU</b>		660	76.200 (3)	95.250 (3) <sup>1)</sup>	44.450 (1) <sup>2)</sup>
Standard mounting dimensions mm		Seal dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_A$ Max.	$r$ as max ( <sup>(*)</sup> )	N	N	rpm		
88	1.5	101 000	215 000	1 100		

Notes: <sup>(\*)</sup> Minimum allowable value of chamfer dimension  $r$ .  
<sup>(\*)</sup> Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952383163
Innendurchmesser	76.2 mm
Außendurchmesser	95.25 mm
Dicke	44.45 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE