

Nadellager NAFW304526-IKO - NAFW304526-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nafw304526-iko>

IKO
NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE
With Inner Ring

| Shaft dia. mm | Identification number | Mess (Ref.) | Boundary dimensions mm | | | | | Standard mounting dimensions mm | | | | |
|-----------------------------|---|---|------------------------|----|----|-----------------------------------|----------------|---------------------------------|---------------------|---------------------|---------------------|------|
| | | g | d | D | C | r _s min ⁽¹⁾ | F _w | d _b | D _s Max. | d _s Min. | D _s Max. | |
| 30 | NAFW 304526 | 155 | 30 | 45 | 26 | 0.3 | 35 | 39.5 | 43 | 32 | 34 | 35.6 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ | Assembled roller ring | | | | | | | | | |
| N | N | rpm | LRT 303526 | | | | | | | | | |
| 26 600 | 51 500 | 14 000 | | | | | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remarks: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952384597 |
| Innendurchmesser | 30 mm |
| Außendurchmesser | 45 mm |
| Dicke | 26 mm |
| Verpackung | 1 |

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE