


Nadellager NAU4919-UU-IKO - NAU4919-UU-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nau4919-uu-iko>

IKO
ROLLER BEARINGS

Caged Roller Bearings **[With Seal]**
Full Complement Roller Bearings **[With Seal]**



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ min	J
95	---	NAU 4919UU	1 270	95	130	35	1.5	106
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _G rpm					
120.5	N 81 000	N 136 000	1 800					

Notes^(*)
(1) Minimum allowable value of chamfer dimension r
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952386560
Innendurchmesser	95 mm
Außendurchmesser	130 mm
Dicke	35 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE