


Nadellager NAU4924-UU-IKO - NAU4924-UU-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nau4924-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings **[With Seal]**
Full Complement Roller Bearings **[With Seal]**



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ min	J
120	---	NAU 4924UU	2 680	120	165	45	1.5	136
E_w	Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed n ₂ rpm					
	153.5	146 000	268 000	1 400				

Notes^(*)
⁽¹⁾ Minimum allowable value of chamfer dimension r
^(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAU and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952386652
Innendurchmesser	120 mm
Außendurchmesser	165 mm
Dicke	45 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE