


# Nadellager

## NAS5009-UU-NR-IKO - NAS5009-UU-NR-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nas5009-uu-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



NAS50-UUNR

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
45	NAS 5009UUNR		0.70	45	75	78.8	40	39	30	4.5
<i>f</i>	<i>c</i>	<i>r</i> mm <sup>(1)</sup>	<i>J</i>	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm				
2	1.5	0.6	56	95 500	144 000	2 000				

Notes<sup>(\*)</sup>  
<sup>(1)</sup> Minimum allowable value of chamfer dimension *r*  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks:  
 1. The NAS and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952386768
Innendurchmesser	45 mm
Außendurchmesser	75 mm
Dicke	40 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE