


# Nadellager

## NAS5032-UU-NR-IKO - NAS5032-UU-NR-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nas5032-uu-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
160	NAS 5032UU	NR	16.5	160	240	248.4	109	108	89	9.5

f	c	r <sub>s</sub> mm	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm
3	3.5	1.5	188.5	720 000	1 390 000	650

Notes<sup>(\*)</sup>  
 (\*) Minimum allowable value of chamfer dimension r  
 (\*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks:  
 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952387093
Innendurchmesser	160 mm
Außendurchmesser	240 mm
Dicke	109 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE