


Nadellager

NAS5048-UU-NR-IKO - NAS5048-UU-NR-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nas5048-uu-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
240	NAS 5048UU	NR	55.5	240	360	376	160	159	130	14.5

f	c	r _s mm	J	Basic dynamic load rating C N	Static load rating C ₀ N	Allowable rotational speed ^(*) rpm
6	4	1.5	278.5	1 570 000	3 350 000	400

Notes^(*)
 (*) Minimum allowable value of chamfer dimension r
 (*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks:
 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952387222
Innendurchmesser	240 mm
Außendurchmesser	360 mm
Dicke	160 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE