


# Nadellager NAS5088-ZZ-IKO - NAS5088-ZZ-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nas5088-zz-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
440		NAS 5088ZZ	310	440	650	—	280	278	—	—

f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm
—	8	3	516	4 570 000	10 900 000	200

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 Remarks: 1. The bearings with seals are provided with prepacked grease.  
 2. The bearings with seals are provided with prepacked grease.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952387413
Innendurchmesser	440 mm
Innendurchmesser	17.323" inch
Außendurchmesser	650 mm
Außendurchmesser	25.591" inch
Dicke	280 mm
Dicke	11.024" inch
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE