

# Nadellager NAXI1223Z-IKO - NAXI1223Z-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/naxi1223z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number									
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D <sub>1</sub>
12		<b>NAXI 1223Z</b>	56.5	—	—	—	—	12	24	28

  

Boundary dimensions mm				Bore chamfer radius mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring						
D <sub>2</sub>	L	B	H			Radial	Axial			Radial	Axial				
25	23	16	9	6.5	0.3	0.2	10	18	9	8 230	10 000	9 190	11 100	9 500	<b>LRT 71016</b>

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
 Remarks: 1. The outer ring has an oil groove and an oil hole.  
 2. Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390697
Innendurchmesser	12 mm
Außendurchmesser	24 mm
Dicke	23 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE