

# Nadellager NBXI1223Z-IKO - NBXI1223Z-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nbxi1223z-iko>

**LINEAR TYPE NEEDLE ROLLER BEARINGS**

Needle Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number												
Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover		Mass (Ref.) g		$d$
---		---		---		<b>NBXI 1223Z</b>		63		12		12
Boundary dimensions mm				Bore diameter mm		Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup>		Assemble
$B$	$H$	$I_1$	$r_{max}$	$r_{min}$	$d_a$	$d_b$	Radial	Axial	Radial	Axial	rpm	LRT 1
16.5	9	6.5	0.3	0.3	15	15	12 300	10 200	14 900	23 900	14 000	LRT 1

Minimum allowable value of chamfer dimension r  
Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBXI series.  
The outer ring has an oil groove and an oil hole.  
Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390710
Innendurchmesser	12 mm
Außendurchmesser	24 mm
Dicke	23 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE