

Nadellager NBXI1425-IKO - NBXI1425-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nbxi1425-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
14	---	---	---	NBXI 1425	70.5	---	14	26	30

Boundary dimensions mm				Bore diameter mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring						
D ₂	L	B	H			Radial	Axial			Radial	Axial				
31	25	17	9	8	0.3	0.3	17	28	16	12 900	11 400	16 300	28 600	13 000	LRT 141717

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
 Remarks: 1. The outer ring has an oil groove and an oil hole.
 2. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390741
Innendurchmesser	14 mm
Innendurchmesser	0.551" inch
Außendurchmesser	26 mm
Außendurchmesser	1.024" inch
Dicke	25 mm
Dicke	0.984" inch
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE