

# Nadellager NAXI1730Z-IKO - NAXI1730Z-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/naxi1730z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number

Shaft dia. mm	Mass (Ref.) g		Mass (Ref.) g		Mass (Ref.) g		d	D	D <sub>i</sub>
	With dust cover	NAXI 1730Z	103	—	With dust cover	—			
17	—	NAXI 1730Z	103	—	—	—	17	30	35

Boundary dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
D <sub>2</sub>	L	B	H		Radial	Axial			Radial
36	30	20.5	10	17 600	14 200	25 400	19 700	7 500	LRT 172020

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390772
Innendurchmesser	17 mm
Außendurchmesser	30 mm
Dicke	30 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE