

# Nadellager NBXI2030-IKO - NBXI2030-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nbxi2030-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>i</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
20	---	---	---	<b>NBXI 2030</b>	171	---	20	37	42

Boundary dimensions mm				Bore diameter mm	Bore diameter mm	Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRT 202520				
D <sub>2</sub>	L	B	H			Radial	Axial	Radial	Axial						
43	30	20.5	11	9.5	0.6	0.3	25	40	24	20 000	22 700	32 100	60 700	9 000	

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390826
Innendurchmesser	20 mm
Außendurchmesser	37 mm
Dicke	30 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE