

Nadellager NBXI2030Z-IKO - NBXI2030Z-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nbxi2030z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g			
20	---	---	---	---	NBXI 2030Z	175	---	20	37	42	

Boundary dimensions mm				Bore diameter mm	Bore diameter mm	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 202520				
D ₂	L	B	H			Radial	Axial	Radial	Axial						
43	30	20.5	11	9.5	0.6	0.3	25	40	24	20 000	22 700	32 100	60 700	9 000	LRT 202520

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390833
Innendurchmesser	20 mm
Außendurchmesser	37 mm
Dicke	30 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE