

Nadellager NAXI2530-IKO - NAXI2530-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/naxi2530-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g			
25	NAXI 2530	179	—	—	—	—	—	—	25	42	47

Boundary dimensions mm				Bore diameter mm	Bore diameter mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring									
D ₂	L	B	H				Radial	Axial			Radial	Axial							
48	30	20.5	11	9.5	0.6	0.3	30	40	25	100	20	400	40	100	33	600	6	500	LRT 253020

Notes:
 (1) Minimum allowable value of chamfer dimension r.
 (2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remark 1: The outer ring has an oil groove and an oil hole.
 2: Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390840
Innendurchmesser	25 mm
Außendurchmesser	42 mm
Dicke	30 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE