

# Nadellager NAXI4032Z-IKO - NAXI4032Z-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/naxi4032z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
40		<b>NAXI 4032Z</b>	324	---	---	---	40	58	65

  

Boundary dimensions mm			r <sup>(1)</sup>	r <sub>max</sub>	r <sub>min</sub>	d <sub>4</sub>	d <sub>5</sub>	Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRT 404520		
D <sub>2</sub>	L	H						Radial	Axial	Radial	Axial				
66.5	32	20	14	9	0.6	0.3	45	57	44	31 000	27 900	60 200	55 100	5 000	LRT 404520

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390970
Innendurchmesser	40 mm
Außendurchmesser	58 mm
Dicke	32 mm
Verpackung	1

[kontakt@123kugellager.de](mailto:kontakt@123kugellager.de)

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE