

Nadellager NBXI4032Z-IKO - NBXI4032Z-IKO

<https://www.123kugellager.de/kugellager-gehauselager/nadellager/radial/nbxi4032z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g				
40	---	---	---	---	NBXI 4032Z	353		40	58	65	

Boundary dimensions mm				Bore diameter mm	Bore diameter mm	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRT 404520				
D ₂	L	B	H			Radial	Axial	Radial	Axial						
66.5	32	20	14	9	0.6	0.3	45	62	44	31 000	40 800	60 200	133 000	5 500	LRT 404520

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390994
Innendurchmesser	40 mm
Außendurchmesser	58 mm
Dicke	32 mm
Verpackung	1

kontakt@123kugellager.de

0800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE